



deanta.co.uk

HOW TO INSTALL AND CARE FOR YOUR DOOR

We offer a limited ten-year warranty on all our doors within our T&Cs. For more information on our warranty and for full terms and conditions please visit our website: www.deantawood.co.uk/

On delivery

Check your doors immediately on arrival and again prior to installation to ensure you are happy with them. * Please note that our timber veneers are a natural product and so colour variation and differing grain patterns are expected.

Storing your doors

Doors must be stored horizontally on a clean, dry, flat and level surface in your home for at least 7 days prior to installation. Please don't store your doors in a freshly plastered room or in an unheated shed or garage.

Finishing your doors

Unfinished oak

You can use any varnish or lacquer suitable for internal joinery. Whatever product you choose make sure to use a fine sandpaper to remove any fine 'hairs' or roughened grain patches before your first coat. We recommend three coats, but please follow the instructions on the product you have purchased.



Finishing your doors

White primed

For a professional finish use a fine sandpaper to smooth any roughened surface/excess primer. Then completing with one to two coats of your chosen finish. If you are choosing a very dark colour you may wish to use specific dark tones undercoat.

Hanging Your Doors

If you need to trim your door to fit it should be immediately revarnished to prevent moisture absorption which may lead to warping or splitting. This includes cut outs for hinges and other ironmongery.

If you have bought a prefinished black or Urban door from us, then we sell touch up pots for repainting trimmed edges and cutouts.

Take no more than the recommended allowance off the width and height of doors in equal amounts on all edges. So, if you need to reduce the width of your door by 20mm you should take 10mm off each side.

Please refer to www.deantawood.co.uk/product-category/internal-doors/ for further details on trimming our range of doors as some doors have different allowances.

We recommend using three hinges to hang all our doors.

Fire Doors

Fire doors are a life-saving product – when installed correctly.

Fire doors should be installed by an experienced carpenter or joiner.

All Deanta UK fire rated products must be used in accordance with the relevant fire certification. Further information on correct installation and field of application process is available upon request from our technical team. Please email: sales@deanta.co.uk

Aftercare

Your door can be dusted down with any soft cloth or use the soft brush attachment on your Hoover. Any marks should be wiped with a damp (not wet) cloth using a warm water. For harder to remove marks or splashes use a mild soap solution in warm water.